



SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product: AIR-SHIELD™ TMP **Part Number:** 6527000
Manufacturer: W. R. MEADOWS, INC. **Address:** 300 Industrial Drive
 Hampshire, Illinois 60140
Telephone: (847) 214-2100 **In case of emergency, dial (800) 424-9300 (CHEMTREC)**
Revision Date: 9/22/2021
Product Use: Permeable Air Barrier

SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

HMIS	HAZARD STATEMENTS
Health	WARNING!
Flammability	May cause skin irritation. (Category 3)
Reactivity	Causes eye irritation. (Category 2B)
Personal Protection	May cause damage to organs through prolonged/repeated exposure. (Category 2)
	PRECAUTIONARY STATEMENTS
	Avoid direct contact.
	Avoid inhalation of mists/aerosols.



SECTION 3: HAZARDS COMPONENTS

Chemical Name:	CAS Number	% by Weight	SARA 313	Vapor Pressure (mm Hg@20°C)	LEL (@25°C)
1. Chloro Alkenes	68527-02-6	1-5	No	N/E	N/E
3. Propylene Glycol	57-55-6	1-5	No	0.01	2.6
4. Isopropyl Alcohol	67-63-0	1-5	Yes	N/E	2
5. Diethylene Glycol Monobutyl Ether	112-34-5	1-5	No	0.02	0.7

N/E = Not Established

This product contains Kaolin Clay and Limestone. These materials contain small amounts of crystalline silica as a naturally occurring component. Exposure to silica is not expected to occur as the product is supplied as a solution. If product is dried/abraded, appropriate protective measures should be taken to prevent exposure to silica.

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush eyes with water for fifteen (15) minutes. If irritation develops/persists, seek medical attention.

SKIN CONTACT: Wash affected areas with mild soap and water. If symptoms persist, seek medical attention.

INHALATION: Remove victim from exposure source and into fresh air. Treat symptomatically.

INGESTION: Seek immediate medical attention. If vomiting spontaneously occurs, keep victim's head below the hips to prevent lung aspiration.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC: See Section Eleven for Symptoms/Effects.

SECTION 5: FIRE AND EXPLOSIVES HAZARDS

FLASHPOINT: >200 °F

EXTINGUISHING MEDIA: Water fog, foam, dry chemical.

CHEMICAL/COMBUSTION HAZARDS: Carbon monoxide, carbon dioxide, and incomplete combustion products.

PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: None recognized.

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Evacuate hazard area of unauthorized personnel. Dike and contain spilled material. Remove source of spill if safe to do so. Soak up spilled material utilizing sand or other suitable absorbent. Place in sealed, marked containers for disposal.

SECTION 7: HANDLING AND STORAGE

SAFE HANDLING PROCEDURES: Avoid direct contact.

SAFE STORAGE: Keep containers closed when not in use. Protect product from freezing

SAFETY DATA SHEET

Date of Preparation: 9/22/21	Page 3 of 3	6527000
SECTION 16: OTHER INFORMATION		
PREPARATION DATE:	9/22/2021	
PREPARED BY:	Dave Carey	

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.
